

Appl. No.: 10/707,922
Amdt. Dated: 8/26/2006
Reply to Office action of: 06/19/2006

AMENDMENTS TO THE SPECIFICATION:

Kindly replace paragraph [0004] with the following amended paragraph:
[0004] Such DV systems typically comprise a first network at 14V used for feeding low consumption loads, for example for lighting and supply of control signals, usually fed in turn from the second network at a higher voltage, typically 42V, through a ~~CC/CC~~ DC/DC electric converter or from a first battery B1. Said second 42V network is used for feeding high consumption loads such as the starter motor, heating system, electromagnetic valve control, motors, such as those for the window control mechanism, seat adjustments, fans, etc. and is fed from a generator G (the vehicle's alternator) or from a second battery B2.

Kindly replace paragraph [0009] with the following amended paragraph:
[0009] British patent application GB 2,342,515 discloses a DV architecture with two networks fed from respective batteries B1, B2, for a motorized vehicle, which, in addition to the generally unidirectional classic ~~CC/CC~~ DC/DC converter for feeding the low voltage network from the higher voltage network, proposes the use of a second bi-directional converter for controlling the status of charge of the two batteries B1 and B2 for the purpose of adjusting the power flows between its inputs/outputs. Said second converter is used when, in addition to normal operation (to feed the lower voltage level network from the higher voltage level network), the low voltage network is fed from the battery connected to the higher voltage branch, the higher voltage network is fed from the two batteries B1, B2, or when battery B1 feeding the low voltage branch is charged from the higher voltage network.

Kindly replace paragraph [0010] with the following amended paragraph:
[0010] Although the use of two shunted converters, as the latter document discloses, is theoretically a feature it shares with the architecture proposed by the present invention, the invention, as will be explained below, is generally based on the use of more than two, one- or two-way ~~CC/CC~~ DC/DC converters, and on a specific way of controlling them to reach a singular purpose, which is the equalization of the outputs of all the converters, the integration of said converter assembly within a sectorial design for the vehicle's power,

Appl. No.: 10/707,922
Amdt. Dated: 8/26/2006
Reply to Office action of: 06/19/2006

and a rating of said converters that is below the requirements of the load set of the sector supplying each one of them. This determines several operating conditions of the electric distribution system where all ~~CC/CC~~ DC/DC converters cooperate, all this non-existent in the technical guidelines disclosed by said British patent application GB 2,342,515.

Kindly replace paragraph [0012] with the following amended paragraph:

[0012] The invention is thus based on an architecture in which the ~~CC/CC~~ DC/DC conversion between the two networks at different voltage levels is subdivided into several shunted ~~CC/CC~~ DC/DC converters, each one of them intended to supply a determined load set of a sector of the automobile. As is well known, such ~~CC/CC~~ DC/DC converters are protected against short circuits consistent with the typical, characteristic V-I curve (foldback curve), such that if a short circuit occurs in any load (not controlled by a controlled switching device such as a SMART FET, relay or similar device) affecting said ~~CC/CC~~ DC/DC converter, the converter will protect the network by setting the voltage to zero and not allowing the supply from the remaining loads. It is evident that in this situation the fuses lose their specific role due to the behavior of the ~~CC/CC~~ DC/DC converter.

Kindly replace paragraph [0013] with the following amended paragraph:

[113] In order to prevent such drawback, according to the invention, the arrangement of a plurality of ~~CC/CC~~ DC/DC converters in shunted connection is proposed, connected to a common point, whose point is likewise connected to the low voltage battery which, in the case of a short circuit, will act on the grounded load's fuse. In this manner, the power to be supplied is shared by the different converters into which it has been divided and the battery which will supply current helping the network if necessary is also shared.

Kindly replace paragraph [0014] with the following amended paragraph:

[0014] In a preferred embodiment of the invention, in which the invention shows its full potential, it has been foreseen that the different ~~CC/CC~~ DC/DC converters dynamically shift their working point in order to achieve the sharing of the same current. For such purposes, a central control, for example according to a master/slave architecture, whose control integrates a master microcontroller, will adjust the different voltage values and

Appl. No.: 10/707,922
Amdt. Dated: 8/26/2006
Reply to Office action of: 06/19/2006

the information of the intensity values required by each load group at the expense of a corresponding ~~CC/CC~~ DC/DC converter (acquired from a detector or a tapping point for each load set) will be exchanged with said control center using a CAN bus or the like.

Kindly replace paragraph [0015] with the following amended paragraph:

[0015] Another feature of the invention is that each one of the converters is intended to feed a series or set of differentiated loads located in different areas of the vehicle, either in the highest voltage level network or in a network at a lower level, according to the power sectorization principle explained above, with the particularity that the ~~CC/CC~~ DC/DC converters used have been designed such that the power that each one of them can supply is less than that of the maximum consumption of all said loads of the specific sector it feeds, such that the power supply to each load set is carried out at specified times at the expense of at least more than one of said different ~~CC/CC~~ DC/DC converters. This follows the consideration that generally, very rarely will consumption on the part of all the system loads, and particularly of the different sectors, occur, which allows rating the converters at a lower value than that which would be necessary considering a simultaneous and continued consumption on the part of all the loads.

Kindly replace paragraph [0016] with the following amended paragraph:

[0016] On the other hand, if several converters are connected at the same point and have as a load, for example, battery B1 which feeds the low voltage network, the power supplied by said battery can be divided by an n factor (depending on the vehicle's number of ~~CC/CC~~ DC/DC converters), such that the converters can be identical and share the same output current. The battery will be responsible for supplying the load for blowing out the fuses. But this architecture will also divide the power conversion in whatever manner necessary.

Kindly replace paragraph [0017] with the following amended paragraph:

[0017] For example, if a 500 W ~~CC/CC~~ DC/DC converter is arranged in the vehicle's compartment but its nearest loads require 600 W, the converter will begin to protect itself by reducing the output voltage (according to a V-I curve of the converter or typical foldback wave); at this moment, the nearest ~~CC/CC~~ DC/DC converter with the lowest

Appl. No.: 10/707,922
Amdt. Dated: 8/26/2006
Reply to Office action of: 06/19/2006

connection resistance to the smart distribution node will supply the remaining necessary power. In this manner, it can be said that, in a static state, the ~~n~~ ~~EC/EC~~ DC/DC converters used (for example 3, one for the motor compartment portion, another for the passenger area, and a third one for the rear portion of the vehicle) will try to share the same amount of power when the power required is close to the maximum of each one of said ~~EC/EC~~ DC/DC converters. In the eventual case that the maximum power of all the converters is exceeded, then battery B1, or battery B2 where applicable, will provide the remaining power required.

Kindly replace paragraph [0018] with the following amended paragraph:

[0018] In a dynamic state (a high speed transient or power fluctuation) and generally with frequencies greater than 100 Hz (for example, during a response to abruptly opening or closing the windows, flashes of light, etc.), a master/slave structure with microprocessor support is necessary so that all the ~~EC/EC~~ DC/DC converters share the same current. Due to all the ~~EC/EC~~ DC/DC converters being located in different areas of the vehicle, a bus, such as a CAN or VAN bus, can inform of the current required by the loads and processed by the different ~~EC/EC~~ DC/DC converters so that the current can be shared in the face of transient phenomena. The speed of the bus and that of the communication protocol controlled by the microprocessor are critical factors, as well as detection method of the current, in order to configure the system according to the proposal of this invention.

Kindly replace paragraph [0019] with the following amended paragraph:

[0019] Such a configuration with several ~~EC/EC~~ DC/DC converters will also allow the converters to share the same thermal overloads due to dissipation, which can be modular.

Kindly replace paragraph [0020] with the following amended paragraph:

[0020] To better understand the invention, a description thereof will be given with reference to several sheets of drawings in which several embodiment examples are shown, which are to be taken as merely illustrative and non-limiting of the scope of the proposed technical guideline. For purposes of simplifying the explanation, said drawings show two networks at different voltage levels, each one of them supporting a series of

Appl. No.: 10/707,922
Amdt. Dated: 8/26/2006
Reply to Office action of: 06/19/2006

sectorized loads associated with the output of a corresponding ~~CC/CC~~ DC/DC converter, although other arrangements, for example only with sectorized loads in the lower voltage level branch, or with only a part of the loads of the upper voltage branch sectorized, fall within the energy distribution system design being referred to.

Kindly replace paragraph [0026] with the following amended paragraph:

[0026] Figure 2 shows a converter's typical V-I curve, or of protection against short circuits, according to which if any load connected to the converter and not protected by a controlled switching device, such as a SMART FET, relay or the like, undergoes a short circuit affecting said ~~CC/CC~~ DC/DC converter, the converter will protect the network by immediately setting the voltage to zero and not allowing the supply from the remaining loads. The shunted arrangement of converters C1, C2, C3 shown in figure 1, connected at a common point to which one of the batteries B1 or B2 is also connected, solves this drawback because the battery acts by blowing out the grounded load's fuse, and the power to be supplied is thus shared by the different converters C1, C2, C3.

Kindly replace paragraph [0028] with the following amended paragraph:

[0028] According to the preferred embodiment of the invention shown in figure 3, it has been foreseen that the ~~CC/CC~~ DC/DC converters shift their working point in order to share the same current, for which purpose a central control M will adjust the different voltage ratings in the nodes to which the respective outputs of the ~~CC/CC~~ DC/DC converters C1, C2, C3 are connected, and the information regarding the intensities required in each one of said nodes will be exchanged using a CAN bus, for example. More specifically, it has been foreseen that the system be implemented in a master/slave architecture in which said control center M integrating the microprocessor establishes itself as master and each one of the converters C1, C2, C3 as slave. Several detectors D1, D2, D3 have been provided for collecting the current required in either of the outputs of each ~~CC/CC~~ DC/DC converter C1, C2, C3, whose information is sent to the control center, where the microcontroller has, for example, a management algorithm loaded into a suitable, programmable memory for distributing the power to be supplied among the different ~~CC/CC~~ DC/DC converters C1-C3 for the purpose of achieving an equalized output from them. Thus, all the ~~CC/CC~~ DC/DC converters used can be equal (in their modular design

Appl. No.: 10/707,922
Amdt. Dated: 8/26/2006
Reply to Office action of: 06/19/2006

principle, leading to reduced manufacturing costs) and, for example, with a power that is lower than that of the load set to be supplied, as indicated in the figures given in this example.

Kindly replace paragraph [0030] with the following amended paragraph:
[0030] Although the arrangement shown in the embodiment example described up to this point with three converters C1, C2, C3 has been designed for a sectorization of the loads of an automotive vehicle in the front portion or motor area, the passenger area, and the rear portion or trunk, which may result to be very convenient, the loads can be sectorized very differently in practice, in a smaller or larger number of groups and also use a smaller or larger number of ~~EC/EC~~ DC/DC converters.